

"t" IP68 waterproof joint





PACKING []/	INNER Dcs	MASTER pcs
Polybag	N/A	N/A





DATI TECNICI / SPECIFICATION / CARACTÉRISTIQUES / CARACTERISTICAS / SPEZIFIKATIONEN

Power supply:	220V AC
Power supply included:	No
Colour:	Black
Guarantee:	2 ANNI
Width (mm):	96
Depth (mm):	82
Height (mm):	30
Net weight kg):	0,055

DESCRIZIONE / DESCRIPTION / DESCRIPTION / DESCRIPCIÓN / BESCHREIBUNG

Excellent material: the connector is made of PA66 + high-strength silicone rubber material, designed for the home, garden or farm; suitable for outdoor lighting with quick connection and external wiring. Professional waterproof design, the degree of waterproofing is IP68 and has fireproof function, dustproof function, shockproof function, these functions ensure that it can be used in the sun or on rainy days. Cable connection: for cables dimensions: H05RN-F 3G1.5mm2 max; t connector, 2 or 3 pin cable connection, very suitable for a quick connection for external lighting and external wiring; max current: 24a and 450v; use temperature: -30 ° c - + 80 ° c. Simple installation: without additional installation tools, a screwdriver can be installed quickly, although non-professionals can also simply install. Other applications in coastal, river, maritime or underwater engineering, underground engineering, mining engineering, solar wind energy, solar water heaters, various carry and equipment.

DATI LOGISTICI / LOGISTIC INFORMATION / DONNEES LOGISTIQUES	S / DATOS LOGISTICOS / LOGISTISCHE DATEN
Tipologia imballo:	Polybag

